

Magellan® 2200VS

Vertical Scanner



Features:

- Aggressive vertical scan volume
- FirstStrike™ advanced decoding software
- Optional Productivity Index Reporting™ Software
- Flash memory for easy software upgrades
- Multiple interface solution supports all popular host interfaces
- Powered auxiliary RS232 port for easy integration of a handheld scanner
- Host diagnostic reporting
- Optional RSS decoding capability
- Optional EAS functionality

Unparalleled Vertical POS Scanning Performance

The Magellan® 2200VS vertical scanner from PSC was designed using the Magellan platform to specifically optimize performance for medium to high throughput applications in grocery, drug, variety, and convenience stores. Unlike competitive vertical scanners, the Magellan 2200VS offers category leading scanning performance, unique value added software features like Productivity Index Reporting™, and our advanced FirstStrike™ decoding software. And because it's based on the Magellan platform, it does so much more.

The Magellan 2200VS has a large, omni-directional scan pattern to maximize productivity and ergonomics for both sweep and presentation scanning methods. And like all Magellan scanners, it offers flash memory for easy software upgrades, supports host diagnostic reporting, and meets all of the Sunrise 2005 initiatives. The Magellan 2200VS also supports the most popular symbologies and offers optional support for RSS.

Smart For Your Business

The Magellan 2200VS was designed to be more than just a bar code scanner. When equipped with Productivity Index Reporting™ (PIR) software, it can identify and track productivity problems with specific items, scanners, lanes, or cashiers. PIR software makes the Magellan 2200VS a versatile tool for increasing productivity at the POS and raises the bar for fixed-position, vertical scanners to a whole new level!

Seamless Integration

Since the Magellan 2200VS is from PSC, you can count on easy installation and years of worry free operation. The Magellan 2200VS boasts a small 6" x 3.8" (15.2 x 9.7 cm) footprint so it will integrate easily into both new and existing point-of-sale configurations. It also supports all of the most popular host terminal interfaces out of the box, including IBM powered USB. In addition, the Magellan 2200VS is compatible with OPOS and JavaPOS systems allowing for even greater installation flexibility at the point of sale.

For fixed-position, vertical scanning, nothing beats the performance and rich feature set of the Magellan 2200VS. Quite simply, it's a Magellan - and nothing beats a Magellan.



Specifications

Magellan® 2200VS

PRODUCT

Mechanical

Height: 6.0" / 15.2 cm
Width: 6.0" / 15.2 cm
Depth: 3.83" / 9.7 cm
Weight: 2.5 lbs. / 1.1 kg

Optical

Presentation
Scan lines: 20
Rate: 6,000 RPM
Depth-of-field: 8.0" / 23.3 cm
Read height: 6.0" / 15.2 cm

Environmental

Temperature rating
Operating: 50° to 104° F / 10° to 40° C
Storage/transport: -40° to 158° F / -40° to 70° C

Humidity:
Operating: 5 to 95% NC
Storage/transport: 5 to 95% NC

Electrical

AC Power requirements
90-265 VAC, 47-63 Hz;
4.0 Watts (nominal),
9.6 Watts (maximum),
2.5 Watts (sleep mode)

Decoding Capability

The Magellan® 2200VS autodiscriminates between all of the following supported symbologies

- UPC Versions A&E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & CI28)
- Reduced Space Symbology Optional (RSS-14 expanded and stacked)
- EAN 8, 13
- JAN 8, 13
- EAN/JAN two label
- UCC/EAN 128
- Code 39 (with full ASCII)
- Code 128
- Code 93
- 1 2 of 5
- Standard 2 of 5
- Italian Pharmcode
- Codabar/NW7
- MSI/Plesley

Communications

Host
Standard RS232, IBM 46XX, IBM USB

Other
Powered RS232 auxiliary port

Safety and Regulatory

Electrical:
EN60 950 (TÜV Europe)
PSC-Mark (Japan); UL 60950 (USA)
CSA 60950 (Canada)

Emissions:
CISPR22-B (World)
FCC part 15 Class B (USA)
VCCI-B (Japan)
EN 55022-B (Europe)
NOM (Mexico)

Laser Safety:
CDRH Class IIa (USA/Canada)
EN 60825-1 Class 1 (Europe)
IEC 60825-1 Class 1 (World)



(CAUTION: Laser Radiation – do not stare into beam);
IEC 60825 Class 1 (Europe)

Other

EAS compatibility
Integrated EAS hardware will work with Counterpoint IV, V, VI and VII models available from Checkpoint® Systems.



Optional Riser Mount



Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 • Email info@opal.ch • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opalsa.ch • Germany • OPAL Associates GmbH • Löhnerhofstrasse 2 • D-78467 Konstanz • Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opalgmbh.de • OPAL Associates GmbH • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email hamburg@opalgmbh.de • Austria • OPAL Associates GesmbH • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opalgmbh.at